

OutRun MINI

**HIGH ACTION ROAD
RACING ADVENTURE!**

SPECIFICATIONS

Outer Dimensions:	32.7 in., 83 cm. (D) 21.7 in., 55 cm. (W) 65 in., 165 cm. (H)
Weight:	211 lbs., 96 kg.
Microprocessors:	16-bit×2; 8-bit×1
Color display capacity:	32-K colors
Program memory:	672-K-byte (max.)
Graphic memory:	1,888-K-byte (max.)
Monitor:	20 inch
Stereo sound:	DA sound system
Stereo music:	FM sound source
Speakers:	10W×2; 4.7 in., 12 cm.
Power supply:	100-240V AC 50/60Hz 165W



PRINTED MATTER: © SEGA 1986

SEGA®

Out Run



DELUXE TYPE



STANDARD TYPE



UPRIGHT TYPE

SPECIFICATIONS

DELUXE TYPE

Outer Dimensions:	77.8 in., 197.5 cm.(D) 46.5 in., 118 cm.(W) 64.4 in., 163.5 cm.(H)
Base Dimensions:	67.5 in., 171.5 cm.×46.5 in., 118 cm.
Weight:	770 lbs., 350 kg.
Microprocessors:	16-bit×2; 8-bit×1
Color display capacity:	32-K colors
Program memory:	672-K-byte (max.)
Graphic memory:	1,888-K-byte (max.)
Monitor:	26 inch
Stereo sound:	DA sound system
Stereo music:	FM sound source
Speakers:	3W output×2; 3.9 in., 10 cm. + 15W output×1; 6.3 in., 16 cm.
Motor:	A DC rolling motor which drives the mechanism.
Power supply:	100-240V AC 50/60Hz 350W

STANDARD TYPE

Outer Dimensions:	68.6 in., 174.0 cm.(D) 44.5 in., 113.0 cm.(W) 66.8 in., 169.5 cm.(H)
Base Dimensions:	66.6 in., 169.0 cm.×37.8 in., 96.0 cm.
Weight:	660 lbs., 300 kg.
Microprocessors:	Same as Deluxe Type
Color display capacity:	Same as Deluxe Type
Program memory:	Same as Deluxe Type
Graphic memory:	Same as Deluxe Type
Stereo sound:	Same as Deluxe Type
Stereo music:	Same as Deluxe Type
Motor:	Same as Deluxe Type
Monitor:	20 inch
Speakers:	3W output×2; 3.9 in., 10 cm.
Power supply:	100-240V AC 50/60Hz 305W

UPRIGHT TYPE

Outer Dimensions:	38.2 in., 97.0 cm.(D) 24.8 in., 63.0 cm. (W) 71.5 in., 181.5 cm. (H)
Weight:	264 lbs., 120 kg.
Microprocessors:	Same as Deluxe Type
Color display capacity:	Same as Deluxe Type
Program memory:	Same as Deluxe Type
Graphic memory:	Same as Deluxe Type
Stereo sound:	Same as Deluxe Type
Stereo music:	Same as Deluxe Type
Monitor:	Same as Standard Type
Speakers:	10W×2; 4.7 in., 12 cm.
Power supply:	100-240V AC 50/60Hz 250W

Design and specifications subject to change without notice. SG-8606E

SEGA®

Sega Enterprises, Ltd.
2-12, Haneda 1-chome, Ota-ku, Tokyo 144, Japan
Tel.:(03)743-7438 Fax:(03)743-5539
Tlx:J22357 SEGASTAR
Sega Enterprises, Inc. (U.S.A.)
2149 Paragon Drive, San Jose, CA 95131
U.S.A. Tel.:(408)435-0201 Fax:(408)435-0294
Sega Europe Limited
410-420 Rayners Lane, Pinner, Middx, HA5
5DY, England Tel.01-868-2331 Tlx:893501
SEGAUK G Fax:01-429-3137

DISTRIBUTED BY:

